

VXT500 VACUUM TRUCK



WEIGHT. Lighter than competing models, our machine delivers a smaller footprint with optimized payload capacity, superior fuel efficiency, and reduced engine and transmission strain, resulting in lower operating costs and longer service life.



SOUND. Less operator fatigue and quieter operation so your project can run smoothly with less disruption to communities.



INTERLOCKS. Enhanced protection for both components and operators, with proactive diagnostics that identify and resolve issues before they escalate-extending component life and maximizing uptime for uninterrupted performance.



SIDE STOW BOOM. Minimizes setup time by keeping the dig tube connected at all times - even during transport - operators can get more work done in a day.



HYDRAULIC DRIVEN WATER PUMP. Eliminates the need for an unloader valve, reducing cost and wear, and consistently maintains set water pressure - even when switching between nozzles.



REVERSE FLOW. Ability to offload material and clear hose clogs, improving efficiency and reducing downtime.

VXT500 VACUUM TRUCK

GENERAL DIMENSIONS	10 CUBIC YARD	12 CUBIC YARD
Length	33 ft 2 in - 34 ft (10 m)	33 ft 7 in - 34 ft (10 m)
Width	102 in (259 cm)	102 in (259 cm)
Height	11 ft 6 in (3.5 m)	11 ft 11 in (3.6 m)
Estimated dry weight	35,300 lb (16,012 kg)	38,800 lb (17,599 kg)

TRUCK SPECS		
Approximate engine horsepower	430 hp	430 hp
GVWR	76,000 lb (34,473 kg)	86,000 lb (39,009 kg)

WATER TANK		
Fresh water capacity	1,000 gal (3,785 L)	1,200 gal (4,542 L)
Water pump flow	19.4 gpm	19.4 gpm
Water pump pressure	3,000 psi (207 bar)	3,000 psi (207 bar)

SPOIL TANK		
Spoil tank capacity	10 yd ³ (7,646 L)	12 yd ³ (9,175 L)
Spoil tank tilt angle	50 degrees	50 degrees

VACUUM		
Air flow	5,018 cfm (142 cubic m/min)	5,018 cfm (142 cubic m/min)
Maximum vacuum	27 inHg (.91 bar)	27 inHg (.91 bar)
Boom reach	16 ft - 25 ft (5m - 8m)	16 ft - 25 ft (5m - 8m)
Boom rotation radius	330 degrees	330 degrees
Door type	Cam-over hydraulic door	Cam-over hydraulic door

OPTIONS	
Hot water heater	590K BTU
Onboard air compressor	
360 camera	
Cold weather option	Heated water plumbing & cabinets
Spoil tank vibrator	
Telematics	

Vermeer MV Solutions, Inc. reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. © 2026 Vermeer MV Solutions, Inc. All Rights Reserved. Printed in the U.S.A. Please recycle.

